



Rostfreier Blankstahl, Rund

EN 10088-3, gezogen, poliert/ geschält, geschliffen Toleranz DIN EN 10278 h9/h11

Stablänge 3-3,3 m, alle Maßangaben in mm

Güte/ Abm.	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	7,0	7,5	8,0	8,5	9,0	9,5	10,0	10,1
1.4301 abgeschreckt	+	o	+	o	+		+		+	+		+	+	+		+	
1.4305 abgeschreckt	+	+	+	+	+	+	+	+	+	+	+	+	+	+		+	
1.4404 abgeschreckt			o		o		+		+			+				+	
1.4541 abgeschreckt					o		o		o	o		+		o		+	
1.4571 abgeschreckt	o	o	+	o	+		+		+	+		+		+		+	

Güte/Abm.	11,0	12,0	12,1	12,3	13,0	14,0	15,0	16,0	17,0	18,0	19,0	20,0	21,0	22,0	23,0	24,0	25,0
1.4301 abgeschreckt	o	+			+	+	+	+	+	+	o	+	o	+	+	+	+
1.4305 abgeschreckt	+	+			+	+	+	+	o	+	+	+	+	+	+	+	+
1.4404 abgeschreckt		+			o	+	+	+		+		+	o	+		+	+
1.4541 abgeschreckt		o			o	+	+	+	o	o	o	+		+		+	+
1.4571 abgeschreckt	o	+			o	+	+	+	+	+	o	+	o	+		+	+

Güte/Abm.	26,0	27,0	28,0	30,0	32,0	34,0	35,0	36,0	38,0	40,0	42,0	45,0	46,0	48,0	50,0	55,0	56,0
1.4301 abgeschreckt	+	o	+	+	+	o	+	+	o	+	+	+		o	+	+	
1.4305 abgeschreckt	+	+	+	+	+	+	+	+	+	+	+	+	o	+	+	+	
1.4404 abgeschreckt	o		+	+	o		+	+	o	+	+	+			+	+	
1.4541 abgeschreckt	o		o	+	+		o	o		+		+			o	+	
1.4571 abgeschreckt	o	o	+	+	+	o	+	+	o	+	+	+		o	+	+	

Güte/Abm.	60,0	65,0	70,0	75,0	80,0	85,0	90,0	95,0	100	110	120
1.4301 abgeschreckt	+	+	+	+	+	o	o	o	o		
1.4305 abgeschreckt	+	+	+	+	+	+	+	o	o		
1.4404 abgeschreckt	+	+	+	o	o						
1.4541 abgeschreckt	o	o	o	o	o	o	o	o	o		
1.4571 abgeschreckt	+	+	+	+	+	o	o	o	o	o	o

+ aus Lagervorrat o aus freibleibendem Werksvorrat

Weitere Abmessungen und Güten auf Anfrage!