



Rundstahl blankgezogen bzw. geschält

DIN EN 10277-2/-3/-4/-5, Toleranz nach DIN EN 10278 h11/h9/h6, Stablänge 3-4 bzw. 6-7 m.

Güte/ Abmessung mm	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5	7,0	7,5	7,95	8,0	8,5
S235JRC+C	+		+	+	+		+		+		+			+	
S355J2C+C									+					+	
Güte/ Abmessung mm	9,0	9,5	9,52	10,0	10,1	10,5	11,0	12,0	12,5	13,0	14,0	14,3	15,0	16,0	17,0
S235JRC+C	o			+			+	+		+	+		+	+	+
S355J2C+C				+				+		o	+		+	+	
Güte/ Abmessung mm	17,5	18,0	19,0	19,5	20,0	21,0	22,0	22,5	23,0	24,0	25,0	26,0	27,0	28,0	29,0
S235JRC+C/+SH		+	o		+	o	+		o	+	+	+		o	
S355J2C+C/+SH		+			+		+			+	+	+		+	
Güte/ Abmessung mm	30,0	32,0	33,0	34,0	35,0	36,0	37,0	38,0	39,0	40,0	41,0	42,0	43,0	44,0	
S235JRC+C/+SH	+	o		+	+	o		o		+		o			
S355J2C+C/+SH	+	+		o	+	+		+		+		+			
Güte/ Abmessung mm	45,0	46,0	47,0	48,0	50,0	51,0	52,0	53,0	54,0	55,0	56,0	58,0	60,0	62,0	
S235JRC+C/+SH	+	o		o	+					o			+	+	
S355J2C+C/+SH	+			o	+					+			+		
Güte/ Abmessung mm	63,0	64,0	65,0	70,0	72,0	75,0	78,0	80,0	85,0	90,0	95,0	100	105	110	
S235JRC+C/+SH			o	o		o		+	+	o	o	+	o	+	
S355J2C+C/+SH			+	+		+		+	o	+		+		+	
Güte/ Abmessung mm	115	120	125	130	140	150	160	180	200						
S235JRC+SH	o	+	o	o	o	+	o								
S355J2C+SH		o		o	o	o	o								

+ aus Lagervorrat o aus freibleibendem Werksvorrat

Weitere Abmessungen und Güten auf Anfrage!